



VIVAX
METROTECH

Live Plug Connector

Technical Specifications V2.5



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-638-7682

Tel : +1-408-962-9990

Fax : +1-408-734-1799

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-1400

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.com

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.com

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
D-96110 Schesslitz

Tel : +49 954 277 227 43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

A. Typical Applications

Item	Parameter
Description	Live Plug Connector (LPC Separation Filter)
Uses	To apply the transmitter signal to target lines carrying up to 240V AC

B. Characteristics

Item	Parameter
Construction	High impact ABS injection molded housing
Weight	0.8lbs (0.36kg)
Dimension	2.5-inch (Dia.) x 6.2-inch (L) (64mm x 156.4mm)
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)
What's in the Box	<ul style="list-style-type: none"> - Live Plug Connector - 3-Pin Power cord (per region) - Quick Guide
External Connectors	1 x XLR 3-Pin plug connects to the transmitter 1 x 3-Pin AC Plug for up to 240V AC
Compatible Transmitters	Loc3 series, Loc series, VM series, vScan

C. Operational

Item	Parameter
Controls	Rotary knob – phase switching
Operating Frequencies	8 kHz, 33 kHz, 65 kHz

D. Shipping and Packaging

Item	Parameter
Shipping Weight	1.4lbs (0.64kg)
Shipping Dimensions	8.7-inch(L) x 5-inch(W) x 2.7-inch(H) (222mm x 127mm x 68mm)

E. Warranty

Item	Parameter
Warranty	12 months

All products are designed and manufactured per ISO 9001:2015.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.