

## A. Typical Applications

Item	Parameter
<b>Description</b>	Live Cable Connector
<b>Uses</b>	The live Cable Connector should only be used by approved operatives adhering to company regulations and work practices while using appropriate safety equipment and clothing. For use on live cables up to 480VAC 60/50Hz.

## B. Live Cable Connector Assembly

Item	Parameter
<b>Construction</b>	Polycarbonate
<b>Weight</b>	1.5lbs (0.7kg)
<b>Dimension</b>	6.3in(L) x 3.1in(W) x 2.2in(H) (160mm x 80mm x 56mm)
<b>Power Supply Options</b>	Transmitter provides power in, the output leads from the separation filter can be connected to conductors carrying up to 480V AC
<b>Compliance/Approvals</b>	<ul style="list-style-type: none"> <li>- Complies with European standard CE (Directive 2004/108/EC) <ul style="list-style-type: none"> <li>• EN 61326-1</li> </ul> </li> <li>- EN 61010-1 EN 61010-2</li> <li>- Complies with FCC Rules Part 15 <ul style="list-style-type: none"> <li>• CATIII</li> <li>• UL94 HB</li> </ul> </li> </ul>

## C. Operational

Item	Parameter
<b>Frequency Range</b>	8.192kHz, 32.768kHz, 8.44kHz SIS
<b>Compatible With Transmitter</b>	Loc-10Tx, Loc-10TxSIS, Loc-5Tx, Loc-1Tx and vScan Tx

## D. Environmental

Item	Parameter
<b>Temperature Range</b>	Operating : -4°F to 122°F (-20°C to 50°C)      Storage : -40°F to 140°F (-40°C to 60°C)
<b>Shipping Weight</b>	2.1lbs (0.94kg)
<b>Shipping Dimension</b>	10in(L) x 9.3in(L) x 3.3in(L) (253mm x 237mm x 84mm)

## E. Warranty

Item	Parameter
<b>Warranty</b>	12 months

Disclaimer: Product and accessory specification and availability information is subject to change without prior notice.

**Vivax-Metrotech Corp. (Headquarters)**  
3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free: +1-800-446-3392  
Tel: +1-408-734-1400  
Fax: +1-408-734-1415  
Email: [sales@vxmt.com](mailto:sales@vxmt.com)  
Website: [www.vivax-metrotech.com](http://www.vivax-metrotech.com)

Please visit [www.vxmt.com](http://www.vxmt.com) for other locations.