

Phase 2 Phase (P2P) Isolating Transformer

Technical Specifications V1.1



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 800-446-3392

Tel : +1-408-734-1400

Fax : +1-408-734-1415

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 800-446-3392

Tel : +1-408-734-1400

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.com

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road,
Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.com

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully,
France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
D-96110 Schesslitz

Tel : +49 954 277 227 43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

A. Typical Applications

Item	Parameter
Description	Phase 2 Phase (P2P) Isolating Transformer
Uses	<p>The Phase to Phase fault locator transformer is used in conjunction with Vivax-Metrotech 10-watt transmitters to trace and pinpoint phase to phase short circuit faults on low voltage three-phase electrical circuits.</p> <p>Please refer to user instructions for detailed instructions on using the P2P.</p>

B. Characteristics

Item	Parameter
Construction	ABS
Weight	5.3lbs (2.4kg)
Dimension	10.6in(L) x 8.5(W) x 4.1in(H) (270mm x 215mm x 105mm)
Display	1.28" 128 x 128 black and white dot matrix LCD
Power Supply	9V DC PP3 battery
Battery	1 x 9V Alkaline (6LR61)
Ingress Protection	IP54 (Lid closed)
Temperature Range	<p>Operating: 0°C to 50°C (+32°F to +122°F)</p> <p>Storage : -20°C to 80°C (-4°F to +176°F)</p>
Connection Cable	<ul style="list-style-type: none"> - Earth Lead - Fused Leads <ul style="list-style-type: none"> • 3.15A, 500V, Very Fast Acting (FF), 6.3 x 32mm, UL recognized - Connection to vLoc Tx Output
LCD	3.5 digit
Maximum Current	1.99A RMS
Compatible Transmitters	<p>Loc-10Tx</p> <p>Loc3-10Tx</p> <p>Loc3-10SiSTx</p>

C. Operational

Phase 2 Phase (P2P) Isolating Transformer "Fault Locate" Output Connection

Item	Parameter
------	-----------

Rated Connection	Rated for connection to CAT III mains circuits up to 500V phase-to-phase
Fuse Rating	3.15A, 500V, Very Fast Acting (FF), 6.3 x 32mm, UL recognized
Fuse Type	ABB/ABB-A 3.15A
Operating Frequency Range	640Hz – 1.5kHz
Maximum Phase to Phase Voltage Differential	20V RMS at 50/60Hz (Fault Locate Output Connection) 500V RMS at 50/60Hz (Trace Output Connection)
Operating Signal Power	10-watts maximum
Optimal Operating Frequency	Trace: 32.768 kHz Fault locate: 640Hz – 1.17kHz

D. Shipping and Packaging

Item	Parameter
Shipping Dimension	14.6in(L) x 9(W) x 4.4in(H) (370mm x 228mm x 112mm)
Shipping Weight	6.33lbs (2.87kg)

E. Warranty

Item	Parameter
Warranty	12 months

All products are designed and manufactured following ISO 9001:2015

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.