



# vCamMX-2

## Mini-Inspection System

- On-screen text writer
- Seven-hour battery life
- On-screen distance, date and time
- Record to USB with SD card backup
- One-touch recording and image capture

The versatile vCamMX-2 mini-inspection camera system is a compact all-in-one inspection camera at an affordable price. Available in two lengths of pushrod and with two sizes of user changeable cameras the system can inspect lines from 1-1/2 to 4"/40 to 100mm. The vCamMX-2 mini-camera has all the features of the larger pushrod camera systems such as locatable sonde, traceable pushrod, distance counter, internal rechargeable batteries and built-in microphone for voice over. The vCamMX-2 can be purchased as a complete all-in-one unit with the control module mounted to the reel or purchase the reel separately to use with the vCam-6 control module.

Internal microphone for audio commenting over recording videos

WIFI - 30' / 10m Range

8" daylight viewable display

Video out through RCA composite socket  
Export distance out and video through mini-USB port

Automatic backup of videos and pictures to SD Card

Large keypad usable while wearing gloves

Locatable three frequency sonde and traceable pushrod

Internal rechargeable battery provides seven-hours of battery life

Field serviceable spring assembly

Choice of two interchangeable camera heads

D18-MX 0.70" / 18mm fixed position camera

Lightweight durable carbon fiber pushrod drum

D26-MX 1" / 26mm self-leveling camera

- One-year warranty covers entire system
- Camera exchange program for out of warranty camera heads

Backed by Vivax-Metrotech's superior dealer network, customer service and service centers.

## Camera Heads

	D26-MX	D18-MX
<b>Application:</b>	2 to 4"/50 to 100mm	1-1/2 to 4"/38 to 100mm
<b>Dimensions:</b>	1.02 x 2"/26 x 55mm	0.70 x 1.2"/18.6 x 29.5mm
<b>Lighting:</b>	20.39 Lumens	17.53 Lumens
<b>Resolution:</b>	700 TVL	520 TVL
<b>Construction:</b>	Stainless-steel housing with Sapphire lens	
<b>Self-leveling:</b>	Yes	No
<b>Environmental:</b>	10 BAR	11 BAR
<b>Focus point:</b>	7.87"/20cm	4.7"/12cm
<b>Field of view:</b>	88.4°	55°

## vCamMX-2 System

<b>Dimensions:</b>	21" (L) x 13" (W) x 25" (H) / 53cm x 33cm x 64cm (with lid closed)
<b>Weight:</b>	100 ft./30m: 30 lbs. / 14kgs. 150 ft./45m: 37 lbs. / 17kgs. (reel, pushrod, control module, and camera)
<b>Construction:</b>	High impact ABS control module, stainless-steel tubular frame, with a carbon fiber drum
<b>Display:</b>	8"/20cm Daylight viewable 800 x 600 TFT LCD display
<b>Battery life:</b>	Eight-hours with sonde off, seven-hours with sonde on
<b>Environmental:</b>	Water resistant to IP65 (light shower with lid closed)

## Type-MX Mini-Reel

The Type-MX mini-reel can be purchased separately without the control attached to use with the vCam-6 or vCam-5 control modules.

			
Type-MX Reel with 100 ft/30m or 150 ft./45m of pushrod.	vCam-6 Control Module	Interconnect plugs into the vCam-6 control module	D26-MX and D18-MX camera heads

Local Vivax-Metrotech Distributor:

## Recommended Locators



VM-540 and vLoc3-Cam

## Popular Accessories



MX Skids



MX Drip bag



Live View Phone and Tablet App

## Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free: 800-446-3392

Tel: +1-408-734-1400

www.vivax-metrotech.com

CONNECT WITH US ON SOCIAL MEDIA



V1.3

Please visit our website for full product specifications.